



Designed By: QT Fabrics





Finished Size: 52" x 59"

FABRIC REQUIREMENTS

	Fabric A 27069 X 1 PANEL		Fabric B* 23692 Y 7/8 YARD		Fabric C 27070 Z 3/8 YARD		Fabric D 27071 PX 1 YARD
	1 BOLT		1 BOLT		1 BOLT		1 BOLT
	Fabric E 27070 B 5/8 YARD		Fabric F** 27070 Z 3 1/2 YARDS	* includes binding ** backing only Additional Supplies Quilt batting, 58" x 65"			
1 BOLT	1 BOLT		3 BOLTS				

* Numbers within gray box = Number of Bolts needed to make 12 Kits

We recommend that you carefully read through all instructions before getting started on your project.

CUTTING DIRECTIONS

Note:

All strips are cut across the width of the fabric (perpendicular to the selvages) unless noted otherwise. All seams are ¼".

WOF = Width of fabric (from selvage to selvage)

Fabric A (27165 Z) panel, cut:

- (1) 32½" x 39½" rectangle.

Fabric B (27165 N) blue pindot, cut:

- (2) 5" x WOF strips; subcut (4) 5" squares, (4) 3" squares, and (4) 2½" squares.
- (6) 2¼" x WOF strips for binding.
- (4) 1" x WOF strips; subcut (2) 1" x 39½" side borders and (2) 1" x 33½" top and bottom borders.

Fabric C (27166 B) white handprint, cut:

- (4) 2½" x WOF strips; subcut (2) 2½" x 40½" side borders and (2) 2½" x 33½" top and bottom borders.

Fabric D (27166 Z) stripe, cut:

- (6) 5" x WOF strips; from 2 strips subcut (2) 5" x 37½" top and bottom borders. Piece remaining strips to make (2) 5" x 44½" side borders.

Fabric E (27167 N) blue handprint, cut:

- (5) 3" x WOF strips; piece strips to make (2) 3" x 53½" side borders and (2) 3" x 46½" top and bottom borders.

CONSTRUCTION

All measurements include ¼" seam allowances.

QUILT ASSEMBLY

Refer to the Quilt Assembly Diagram for the following steps.

1. Sew the 1" x 39½" Fabric B strips to the sides of the center panel, and then sew the 1" x 33½" Fabric B strips to the top and bottom.
2. Sew the 2½" x 40½" Fabric C strips to the sides of the quilt center.
3. Sew a 2½" Fabric B square to each end of the 2½" x 33½" Fabric C strips. Sew the pieced strips to the top and bottom of the quilt center.

4. Sew the 5" x 44½" Fabric D strips to the sides of the quilt.

5. Sew a 5" Fabric B square to each end of the 5" x 37½" Fabric D strips. Sew the pieced strips to the top and bottom of the quilt.

6. Sew the 3" x 53½" Fabric E strips to the sides of the quilt.

7. Sew a 3" Fabric B square to each end of the 3" x 46½" Fabric E strips. Sew the pieced strips to the top and bottom of the quilt.



Quilt Assembly Diagram

FINISHING

1. Cut backing fabric into (2) 1¾-yard pieces. Join the pieces along their length.
2. Layer the backing, batting, and quilt top; baste. Quilt as desired.
3. Make double-fold binding using the 2¼"-wide Fabric B strips. Sew binding to quilt using your preferred method.

While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies.