




FINISHED SIZE 6½" x 10"



## FABRIC REQUIREMENTS

	<b>Fabric A</b> <b>31199 B</b> <b>¼ YARD</b>		<b>Fabric B</b> <b>31201 EX</b> <b>¼ YARD*</b>	<b>* coordinating fabric for lining</b>  <b>ADDITIONAL MATERIALS</b> <ul style="list-style-type: none"> <li>• ¼ yard of fusible interfacing (optional).</li> <li>• 12" or longer coordinating zipper.</li> </ul>
---	--	---	--	--

 Information within gray box = Number of Bolts or Packs needed to make 12 Kits

*We recommend that you carefully read through all instructions before starting your project.*

## CUTTING

**Fabric A (exterior)**, cut:

- (2) 7½" x 11" rectangles.

**Fabric B (lining)**, cut:

- (2) 7½" x 11" rectangles.

**Interfacing (if using)**, cut:

- (2) 7½" x 11" rectangles.

## SEWING

**Use a ¼" seam allowance except where noted.**

1. Apply the **Interfacing** to the wrong side of the **Fabric A** pieces.
2. Lay a **Fabric A** piece and a **Fabric B** piece down with right sides together.
3. On the long edge, sandwich the zipper between **Fabric A/B piece** with the right side of the zipper facing the **Fabric A piece** extending the ends of the zipper beyond the fabric for smooth stitching.



4. Using a zipper foot, stitch close to the zipper teeth, bring wrong sides together and press.
5. Repeat steps 3 and 4 for the other **Fabric A** and **Fabric B** pieces being careful to line up the side edges.
6. Unzip the zipper to the middle of the bag.
7. With **Fabric B** face up (**Fabric A** on the inside), match side seams and bottom seam and machine stitch around using a ½" seam allowance. Reinforce stitching at the zipper on both sides.
8. Clip extra zipper and bottom corners to reduce bulk being careful to not cut the stitching. Turn right side out.

*While all possible care has been taken to ensure the accuracy of this pattern, we are not responsible for printing errors or the way in which individual work varies.*